

Tubi elettrouniti in acciaio inossidabile solubilizzati in lunghezze commerciali  
Specifiche di produzione ASTM A 312

*Stainless steel welded pipe annealed in random length mm 6000*  
According to standards ASTM A 312

DIAMETRI / OD	Th. 2,00		Th. 3,00		SCH 10S		SCH 40S	
	mm	Th mm	Kg/mt	Th mm	Kg/mt	Th mm	Kg/mt	Th mm
21,34	2,00	0,97	3,00	1,38	2,11	1,02	2,77	1,29
26,67	2,00	1,24	3,00	1,78	2,11	1,30	2,87	1,71
33,40	2,00	1,57	3,00	2,28	2,77	2,12	3,38	2,54
42,16	2,00	2,01	3,00	2,94	2,77	2,73	3,56	3,44
48,30	2,00	2,32	3,00	3,40	2,77	3,16	3,68	4,11
60,33	2,00	2,92	3,00	4,31	2,77	3,99	3,91	5,52
76,10	2,00	3,71	3,00	5,49				
88,90	2,00	4,35	3,00	6,45	3,05	6,56	5,49	11,47
114,30	2,00	5,62	3,00	8,36	3,05	8,50	6,02	16,32
141,30					3,40	11,74	6,55	22,10
168,30					3,40	14,04	7,11	28,70
219,10					3,76	20,27	8,18	43,20

Disponibile in stock AISI 304L - 316L EN 1,4307 - 1,4404  
Available from stock AISI 304L - 316L EN 1,4307 - 1,4404

Disponibile in 30 gg AISI 304L - 316L EN 1,4307 - 1,4404  
Delivery in four weeks AISI 304L - 316L EN 1,4307 - 1,4404



Santarella Srl

Via Carabelli, 12 - 21012 Cassano Magnago (VA) - Italy - (Highway A8 - Milano/Laghi - exit Busto Arsizio)  
Tel. +39.0331.717411 - Fax +39.0331.717440 - www.santarella.com - info@santarella.com  
Cap. Soc. € 4.500.000,00 i.v. R.E.A VARESE 190427 Reg. Impr. trib. Busto A. 18174 C.F. & P.IVA IT 01559380124