

Tubi senza saldatura in acciaio inossidabile in lunghezze commerciali
Specifiche di produzione ASTM A 312

Stainless steel seamless pipe in random length mm 6000
According to standards ASTM A 312

DIAMETRI / OD	SCH 10S		SCH 40S		SCH 80S	
	mm	Th mm	Kg/mt	Th mm	Kg/mt	Th mm
17,15	1,65	0,64	2,31	0,86		
21,34	2,11	1,02	2,77	1,29	3,73	1,64
26,67	2,11	1,30	2,87	1,71	3,91	2,23
33,40	2,77	2,12	3,38	2,54	4,55	3,29
42,16	2,77	2,73	3,56	3,44	4,85	4,53
48,30	2,77	3,16	3,68	4,11	5,08	5,50
60,33	2,77	3,99	3,91	5,52	5,54	7,60
73,03	3,05	5,34	5,16	8,77	7,01	11,59
88,90	3,05	6,56	5,49	11,47	7,62	15,51
101,60	3,05	7,53	5,74	13,78	8,08	18,92
114,30	3,05	8,50	6,02	16,32	8,56	22,66
141,30	3,40	11,74	6,55	22,10	9,52	31,41
168,30	3,40	14,04	7,11	28,70	10,97	43,22
219,10	3,76	20,27	8,18	43,20	12,70	65,64

Disponibile in stock AISI 304L - 316L EN 1,4307 - 1,4404
 Available from stock AISI 304L - 316L EN 1,4307 - 1,4404

Disponibile in 30 gg AISI 304L - 316L EN 1,4307 - 1,4404
 Delivery in four weeks AISI 304L - 316L EN 1,4307 - 1,4404

Tubi senza saldatura in acciaio inossidabile in lunghezze commerciali
Specifiche di produzione ASTM A 213

Stainless steel seamless pipe in random length mm 6000
According to standards ASTM A 213

DIAMETRI / OD	SPESSORI / TH mm			
	mm	1,00	1,50	2,00
6,00	0,13	0,17		
8,00	0,18	0,24		
10,00	0,23	0,32	0,40	
12,00	0,28	0,39	0,50	
14,00	0,33	0,47	0,60	

Disponibile in stock AISI 316L EN 1,4404
 Available from stock AISI 316L EN 1,4404

Disponibile in 30 gg AISI 316L EN 1,4404
 Delivery in four weeks AISI 316L EN 1,4404

